

WYRESTORM EXPRESS HIGH SPEED HDMI CABLES

EXP-HDMI-0.5M / EXP-HDMI-1.0M /
EXP-HDMI-3.0M / EXP-HDMI-5.0M

WyreStorm Express is a plug and play range of high definition HDMI distribution solutions for the home or any venue that make everyday video connectivity and setup, simple.

WyreStorm Express products offer straight-forward HD switching, distribution, IR control and cable solutions, all 3D compatible and designed to work with the latest video source components (satellite and cable boxes), gaming devices and flat panel TV displays.



Cable Lengths Available

WyreStorm Express 0.5M HDMI Cable - EXP-HDMI-0.5M
WyreStorm Express 1.0M HDMI Cable - EXP-HDMI-1.0M
WyreStorm Express 3.0M HDMI Cable - EXP-HDMI-3.0M
WyreStorm Express 5.0M HDMI Cable - EXP-HDMI-5.0M

WyreStorm Express cables are HDMI v.4 certified and transmit high-definition digital audio and video signals without quality loss or distortion. The cables feature high-purity copper, gold plated connectors and tin plated conduits all securely welded and fully shielded thanks to a durable, foil-insulated cable housing. WyreStorm Express cables are the ideal choice for simple, reliable and affordable connection of any HDMI source input or display output up to 5m.

KEY FEATURES

- 99.999% oxygen free copper conductors
- Flexible, durable foil-insulated housing material increases ease of installation and product life.
- Exceptional high speed performance for 1080p displays, with 3D displays and 4K compatibility
- High definition metal plug
- Perfect opaque plug end as well as excellent conductivity and protection against oxidation.
- Kink protection and strain relief to protect the conductor.

IN THE BOX

1 x HDMI Cable



US OFFICE:
TEL: +1 901 384 3575
FAX: +1 901 384 3574

EMEA OFFICE:
TEL: + 44 (0) 1793 230 343
FAX: + 44 (0) 1793 230 583

SPECIFICATIONS

Lengths:	0.5m / 1.64ft, 1.0m / 3.28ft, 3.0m / 9.84ft, 5.0m / 16.4ft
Weight (Kg):	47g / 1.65oz, 78g / 2.75lb, 180g / 6.34lb, 310g / 10.93lb
Operating Temperature Range:	0 to +35°C (32 to +95°F)
Operating Humidity Range:	5 to 90 % RH (no condensation)
Input Video Signal:	0.5-1.0 volts p-p
Input DDC Signal:	5 volts p-p (TTL)
Maximum Single Link Range:	1080p 36bit Deep Colour @ 60 fps
Video Format Supported:	VESA: 640x480, 800x600, 1024x768, 1280x1024, 1600x1200, 1920x1200 DTV/HDTV: 480i/576i/480p/576p/720p/1080i/1080p
Output Video:	HDMI v1.4 with full 3D compatibility with Frame packing/sequential (Blu-ray) and Interlaced Stereoscopic (satellite/cable broadcasts)
Audio Format Supported:	DTS-HD, Dolby True HD, multi-channel 5.1, 7.1, stereo - SPDIF Audio: Dolby Digital PCM 5.1
Power Consumption:	0 Watts (Max.)
BTU Rating:	000.0